NSBOCD S/N 686366 02/01/2020 Hobbs:2012.2 Removed, cleaned, inspected, gapped, tested and reinstalled all spark plugs with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-70/80, 3-68/80, 4-72/80, 5-70/80, 6-70/80. Min pressure for the day was 45. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual-inspection and found to be Airworthy. –end- N880CD S/N 686366 04/02/2021 Hobbs:2030.3 total:2030.3 Removed and inspected all spark plugs found worn to limits install new sparkplugs P/N URHB32E with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-70/80, 6-72/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. –end- N880CD S/N 686366 05/20/2022 Hobbs:2053.5 total:2053.5 Removed, cleaned, tested and reinstalled all spark plugs. Replaced airfilter element with new element p/n BA-24. Compression check 1-70/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drainder engine oil, removed and engin	Ight Forward N880CD S/N 686366 02/01/2020 Hobbs:2012.2 total:2012.2 Removed, cleaned, inspected, gapped, tested and reinstalled all spark plugs with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-70/80, 3-68/80, 4-72/80, 5-70/80. For/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual-inspection and found to be Airworthy. —end- N880CD S/N 686366 04/02/2021 Hobbs:2030.3 total:2030.3 Removed and inspected all spark plugs found worn to limits install new sparkplugs P/N URHB32E with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-70/80, 6-72/80. Min pressure for the day was 46, Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. —end- N880CD S/N 686366 05/20/2022 Hobbs:2053.5 total:2053.5 Removed, cleaned, tested and reinstalled all spark plugs. Replaced airfilter element with new element p/n BA-24. Compression check 1-70/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted installed engine oil, removed and inspected oil filter no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. OranGuard. Removed exhaus tystem.	Date	Total Time		me Time Since Last Overhaul		Engine Service and Maintenance Record		
N880CD S/N 686366 02/01/2020 Hobbs:2012.2 total:2012.2 Removed, cleaned, inspected, gapped, tested and reinstalled all spark plugs with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-70/80, 3-68/80, 4-72/80, 5-70/80, 6-70/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual-inspection and found to be Airworthy. —end- N880CD S/N 686366 04/02/2021 Hobbs:2030.3 total:2030.3 Removed and inspected all spark plugs found worn to limits install new sparkplugs P/N URHB32E with new gaskets. Replaced ailfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-70/80, 6-72/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter not defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. —end- Stewart Pruitt 2644624 A&P/IA N880CD S/N 686366 05/20/2022 Hobbs:2053.5 total:2053.5 Removed, cleaned, tested and reinstalled all spark plugs. Replaced airfilter element with new element p/n BA-24. Compression check 1-79/80, 2-64/80, 3-68/80, 4-79/80, 5-68/80, 6-70/80. Min pressure for the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed, and inspected oil filter no defects	N880CD S/N 686366 02/01/2020 Hobbs:2012.2 total:2012.2 Removed, cleaned, inspected, gapped, tested and reinstalled all spark plugs with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-70/80, 3-68/80, 4-72/80, 5-70/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual-inspection and found to be Airworthy. —end- N880CD S/N 686366 04/02/2021 Hobbs:2030.3 total:2030.3 Removed and inspected all spark plugs found worn to limits install new sparkplugs P/N URHB32E with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-70/80, 6-72/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 ylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. —end- Stewart Pruitt 2644624 A&P/IA N880CD S/N 686366 05/20/2022 Hobbs:2053.5 total:2053.5 Removed, cleaned, tested and reinstalled all spark plugs. Replaced airfilter element with new element p/n BA-24. Compression check 1-70/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Removed exhaust system. Collector p/n 1355-001 and min pipe p/n 1375-003 repaired by Aerospace Wel		Hrs.	Min.	Hrs.	Min.	Modifications and Service Bulletins		
Removed, cleaned, inspected, gapped, tested and reinstalled all spark plugs with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-70/80, 3-68/80, 4-72/80, 5-70/80, 6-70/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50v oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. Lecrify that this engine has been inspected in accordance with an Annual-inspection and found to be Airworthy. —end- N80CD S/N 686366 04/02/2021 Hobbs:2030.3 total:2030.3 Removed and inspected all spark plugs found worn to limits install new sparkplugs P/N URHB32E with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 7-2/80, 5-72/80, 6-72/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. Lecrify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy.—end- M80CD S/N 686366 05/20/2022 Hobbs:2053.5 total:2053.5 Removed, cleaned, tested and reinstalled all spark plugs. Replaced airfilter element with new element p/n BA-24. Compression check 1-70/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Drained engine oil, nemoved and inspected oil filter no defects noted. Drained en	Hobbs:2012.2 Removed, cleaned, inspected, gapped, tested and reinstalled all spark plugs with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-70/80, 3-68/80, 4-72/80, 5-70/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. Lecrtify that this engine has been inspected in accordance with an Annual-inspection and found to be Airworthy. – end- N880CD S/N 686366 04/02/2021 Hobbs:2030.3 total:2030.3 Removed and inspected all spark plugs found worn to limits install new sparkplugs P/N URHB32E with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-70/80. 6-72/80. 5 min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. Lecrtify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. —end- N880CD S/N 686366 05/20/2022 Hobbs:2053.5 total:2053.5 Removed, cleaned, tested and reinstalled all spark plugs. Replaced airfilter element with new element p/n BA-24. Compression check 1-70/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed engine oil, removed and inspected oil filter no defects noted. Ins	rought Forward		→					
Removed, cleaned, inspected, gapped, tested and reinstalled all spark plugs with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-70/80, 3-68/80, 4-72/80, 5-70/80, 6-70/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual-inspection and found to be Airworthy. —end- N880CD S/N 686366 04/02/2021 Hobbs:2030.3 total:2030.3 Removed and inspected all spark plugs found worn to limits install new sparkplugs P/N URHB32E with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-70/80, 6-72/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. —end- Stewart Pruitt 2644624 A&P/IA N880CD S/N 686366 05/20/2022 Hobbs: 2053.5 total: 2053.5 Removed, cleaned, tested and reinstalled all spark plugs. Replaced airfilter element with new element p/n BA-24. Compression check 1-70/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for the day was 46, Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil,	Removed, cleaned, inspected, gapped, tested and reinstalled all spark plugs with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-70/80, 3-68/80, 4-72/80, 5-70/80, 6-70/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual-inspection and found to be Airworthy. —end- Stewart Pruitt 2644624 A&P/IA N880CD S/N 686366 04/02/2021 Hobbs:2030.3 total:2030.3 Removed and inspected all spark plugs found worn to limits install new sparkplugs P/N URHB32E with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-70/80, 6-72/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy.—end- N880CD S/N 686366 05/20/2022 Hobbs:2053.5 total:2053.5 Removed, cleaned, tested and reinstalled all spark plugs. Replaced airfilter element with new element p/n BA-24. Compression check 1-70/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n AA48109 and serviced en		N8	80CD	S	/N 6863	66 02/01/2020		
Removed, cleaned, inspected, gapped, tested and reinstalled all spark plugs with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-70/80, 3-68/80, 4-72/80, 5-70/80, 6-70/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual-inspection and found to be Airworthy. –end- N880CD S/N 686366 04/02/2021 Hobbs:2030.3 total:2030.3 Removed and inspected all spark plugs found worn to limits install new sparkplugs P/N URHB32E with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-70/80, 6-72/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. –end— Stewart Pruitt 2644624 A&P/IA N880CD S/N 686366 05/20/2022 Hobbs:2053.5 total:2053.5 Removed, cleaned, tested and reinstalled all spark plugs. Replaced airfilter element with new element p/n BA-24. Compression check 1-70/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected provided provided engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. R	Removed, cleaned, inspected, gapped, tested and reinstalled all spark plugs with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-70/80, 3-68/80, 4-72/80, 5-70/80, 6-70/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual-inspection and found to be Airworthy. —end- Stewart Pruitt 2644624 A&P/IA N880CD S/N 686366 04/02/2021 Hobbs:2030.3 total:2030.3 Removed and inspected all spark plugs found worn to limits install new sparkplugs P/N URHB32E with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-70/80, 6-72/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy.—end- N880CD S/N 686366 05/20/2022 Hobbs:2053.5 total:2053.5 Removed, cleaned, tested and reinstalled all spark plugs. Replaced airfilter element with new element p/n BA-24. Compression check 1-70/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n AA48109 and serviced en						- L2012 2		
gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-69/60, 2-70/80, 3-68/80, 4-72/80, 5-70/80, 6-70/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. —end- N880CD S/N 686366 04/02/2021 Hobbs:2030.3 total:2030.3 Removed and inspected all spark plugs found worn to limits install new sparkplugs P/N URHB32E with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-72/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. —end- Washeld Discovers of the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Oil not be a province of the day was 46. Performed boroscope inspection of all 6 cylinders, noted and reinstalled all spark plugs. Replaced airfilter element with new element p/n BA-24. Compression check 1-70/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter n	gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-69/60, 2-70/80, 3-68/80, 4-72/80, 5-70/80, 6-70/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual-inspection and found to be Airworthy. –end- N880CD S/N 686366 04/02/2021 Hobbs:2030.3 total:2030.3 Removed and inspected all spark plugs found worn to limits install new sparkplugs P/N URHB32E with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-70/80, 6-72/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. Lecrify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. –end- Stewart Pruitt 2644624 A&P/IA N880CD S/N 686366 05/20/2022 Hobbs:2053.5 total:2053.5 Removed, cleaned, tested and reinstalled all spark plugs. Replaced airfilter element with new element p/n BA-24. Compression check 1-70/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n AA443(09 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Removed exhaust system. Co					-			
N880CD S/N 686366 04/02/2021 Hobbs:2030.3 total:2030.3 Removed and inspected all spark plugs found worn to limits install new sparkplugs P/N URHB32E with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-70/80, 6-72/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. —end- N880CD S/N 686366 05/20/2022 Hobbs:2053.5 total:2053.5 Removed, cleaned, tested and reinstalled all spark plugs. Replaced airfilter element with new element p/n BA-24. Compression check 1-70/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n AA48109 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Removed exhaust system. Collector p/n engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Removed exhaust system. Collector p/n gaskets for nbr1/3/4/5 cylinders using new gaskets p/n 668893. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. Leertify that this engine has	N880CD S/N 686366 04/02/2021 Hobbs:2030.3 total:2030.3 Removed and inspected all spark plugs found worn to limits install new sparkplugs P/N URHB32E with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-70/80, 6-72/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy.—end— Stewart Pruitt 2644624 A&P/IA N880CD S/N 686366 05/20/2022 Hobbs:2053.5 total:2053.5 Removed, cleaned, tested and reinstalled all spark plugs. Replaced airfilter element with new element p/n BA-24. Compression check 1-70/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n AA48109 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Removed exhaust system. Collector p/n 13535-001 and mid pipe p/n 13755-003 repaired by Aerospace Welding Minneapolis on work orders 209435 and 209436. Reinstalled exhaust system using new gaskets p/n 658458. Replaced valve cover gaskets for nbr1/3/4/5 cylinders using new gaskets p/n 668893. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy.—end-		gas 2-7 bo ins en	skets. Ro 70/80, 3 roscope spected gine with	eplaced a -68/80, 4 inspecti oil filter th Aeros	airfilter e 4-72/80, ion of all no defec hell 15w- s noted.	element with new element p/n BA-24. Compression check 1-08/80, 5-70/80, 6-70/80. Min pressure for the day was 46. Perform 6 cylinders, no defects noted. Drained engine oil, removed and its noted. Installed new oil filter p/n CH48109-1 and serviced 50w oil. Added 1 pint of CamGuard. Ran engine and performed Installed engine cowling. All AD's current as of this date. I certify		
Stewart Pruitt 2644624 A&P/IA N880CD S/N 686366 04/02/2021 Hobbs:2030.3 total:2030.3 Removed and inspected all spark plugs found worn to limits install new sparkplugs P/N URHB32E with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-70/80, 6-72/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. —end———————————————————————————————————	N880CD S/N 686366 04/02/2021 Hobbs:2030.3 total:2030.3 Removed and inspected all spark plugs found worn to limits install new sparkplugs P/N URHB32E with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-70/80, 6-72/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy.—end———————————————————————————————————					as been ii	nspected in accordance with an Affilia Hispection and Journal to 25		
N880CD S/N 686366 04/02/2021 Hobbs:2030.3 total:2030.3 Removed and inspected all spark plugs found worn to limits install new sparkplugs P/N URHB32E with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-70/80, 6-72/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. —end———————————————————————————————————	N880CD S/N 686366 04/02/2021 Hobbs:2030.3 total:2030.3 Removed and inspected all spark plugs found worn to limits install new sparkplugs P/N URHB32E with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-70/80, 6-72/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. —end———————————————————————————————————		Ai	rworthy	, –end-		Hur Educt		
Removed and inspected all spark plugs found worn to limits install new sparkplugs P/N URHB32E with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-70/80, 6-72/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. —end- Stewart Pruitt 2644624 A&P/IA N880CD S/N 686366 05/20/2022 Hobbs:2053.5 total:2053.5 Removed, cleaned, tested and reinstalled all spark plugs. Replaced airfilter element with new element p/n BA-24. Compression check 1-70/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n AA48109 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Removed exhaust system. Collector p/n 13535-001 and mid pipe p/n 13755-003 repaired by Aerospace Welding Minneapolis on work orders 209435 and 209436. Reinstalled exhaust system using new gaskets p/n 652458. Replaced valve cover gaskets for nbr1/3/4/5 cylinders using new gaskets p/n 668893. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has	Removed and inspected all spark plugs found worn to limits install new sparkplugs P/N URHB32E with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-70/80, 6-72/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. —end———————————————————————————————————	-					Stewart Pruitt 2644624 A&P/IA	-	
Removed and inspected all spark plugs found worn to limits install new sparkplugs P/N URHB32E with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-70/80, 6-72/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. —end- Stewart Pruitt 2644624 A&P/IA N880CD S/N 686366 05/20/2022 Hobbs:2053.5 total:2053.5 Removed, cleaned, tested and reinstalled all spark plugs. Replaced airfilter element with new element p/n BA-24. Compression check 1-70/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n AA48109 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Removed exhaust system. Collector p/n 13535-001 and mid pipe p/n 13755-003 repaired by Aerospace Welding Minneapolis on work orders 209435 and 209436. Reinstalled exhaust system using new gaskets p/n 652458. Replaced valve cover gaskets for nbr1/3/4/5 cylinders using new gaskets p/n 668893. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has	Removed and inspected all spark plugs found worn to limits install new sparkplugs P/N URHB32E with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-70/80, 6-72/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. —end———————————————————————————————————		+			-			
Removed and inspected all spark plugs found worn to limits install new sparkplugs P/N URHB32E with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-70/80, 6-72/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. —end- Stewart Pruitt 2644624 A&P/IA N880CD S/N 686366 05/20/2022 Hobbs:2053.5 total:2053.5 Removed, cleaned, tested and reinstalled all spark plugs. Replaced airfilter element with new element p/n BA-24. Compression check 1-70/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n AA48109 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Removed exhaust system. Collector p/n 13535-001 and mid pipe p/n 13755-003 repaired by Aerospace Welding Minneapolis on work orders 209435 and 209436. Reinstalled exhaust system using new gaskets p/n 652458. Replaced valve cover gaskets for nbr1/3/4/5 cylinders using new gaskets p/n 668893. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has	Removed and inspected all spark plugs found worn to limits install new sparkplugs P/N URHB32E with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-70/80, 6-72/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. —end———————————————————————————————————		NOSOCD		C/N 69	6366	04/02/2021		
Removed and inspected all spark plugs found worn to limits install new sparkplugs P/N URHB32E with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-70/80, 6-72/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. —end-Stewart Pruitt 2644624 A&P/IA N880CD S/N 686366 05/20/2022 Hobbs:2053.5 total:2053.5 Removed, cleaned, tested and reinstalled all spark plugs. Replaced airfilter element with new element p/n BA-24. Compression check 1-70/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n AA48109 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Removed exhaust system. Collector p/n 13535-001 and mid pipe p/n 13755-003 repaired by Aerospace Welding Minneapolis on work orders 209435 and 209436. Reinstalled exhaust system using new gaskets p/n 652458. Replaced valve cover gaskets for nbr1/3/4/5 cylinders using new gaskets p/n 668893. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has	Removed and inspected all spark plugs found worn to limits install new sparkplugs P/N URHB32E with new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-70/80, 6-72/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. —end———————————————————————————————————		N88UCD		3/14 00	0300	04/02/2021		
new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-70/80, 6-72/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. —end- Stewart Pruitt 2644624 A&P/IA N880CD S/N 686366 05/20/2022 Hobbs:2053.5 total:2053.5 Removed, cleaned, tested and reinstalled all spark plugs. Replaced airfilter element with new element p/n BA-24. Compression check 1-70/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n AA48109 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Removed exhaust system. Collector p/n 13535-001 and mid pipe p/n 13755-003 repaired by Aerospace Welding Minneapolis on work orders 209435 and 209436. Reinstalled exhaust system using new gaskets p/n 652458. Replaced valve cover gaskets for nbr1/3/4/5 cylinders using new gaskets p/n 668893. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has	new gaskets. Replaced airfilter element with new element p/n BA-24. Compression check 1-68/80, 2-64/80, 3-68/80, 4-72/80, 5-70/80, 6-72/80. Min pressure for the day was 46. Perform boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. —end———————————————————————————————————		Hobbs:20	30.3		total:2	030.3		
Removed, cleaned, tested and reinstalled all spark plugs. Replaced airfilter element with new element p/n BA-24. Compression check 1-70/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n AA48109 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Removed exhaust system. Collector p/n 13535-001 and mid pipe p/n 13755-003 repaired by Aerospace Welding Minneapolis on work orders 209435 and 209436. Reinstalled exhaust system using new gaskets p/n 652458. Replaced valve cover gaskets for nbr1/3/4/5 cylinders using new gaskets p/n 668893. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has	Removed, cleaned, tested and reinstalled all spark plugs. Replaced airfilter element with new element p/n BA-24. Compression check 1-70/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n AA48109 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Removed exhaust system. Collector p/n 13535-001 and mid pipe p/n 13755-003 repaired by Aerospace Welding Minneapolis on work orders 209435 and 209436. Reinstalled exhaust system using new gaskets p/n 652458. Replaced valve cover gaskets for nbr1/3/4/5 cylinders using new gaskets p/n 668893. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. —end-		64/80, 3- inspection defects in Added 1 cowling.	68/80, 4 on of all 6 noted. Ins pint of C All AD's	-72/80, 5 cylinders stalled ne amGuard current	-70/80, 6- s, no defe w oil filter l. Ran eng as of this	-72/80. Min pressure for the day was 46. Perform boroscope cts noted. Drained engine oil, removed and inspected oil filter no rp/n CH48109-1 and serviced engine with Aeroshell 15w-50w oil. gine and performed leak check no leaks noted. Installed engine date. I certify that this engine has been inspected in accordance with the Airworthy.—end-		
Removed, cleaned, tested and reinstalled all spark plugs. Replaced airfilter element with new element p/n BA-24. Compression check 1-70/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n AA48109 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Removed exhaust system. Collector p/n 13535-001 and mid pipe p/n 13755-003 repaired by Aerospace Welding Minneapolis on work orders 209435 and 209436. Reinstalled exhaust system using new gaskets p/n 652458. Replaced valve cover gaskets for nbr1/3/4/5 cylinders using new gaskets p/n 668893. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has	Removed, cleaned, tested and reinstalled all spark plugs. Replaced airfilter element with new element p/n BA-24. Compression check 1-70/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n AA48109 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Removed exhaust system. Collector p/n 13535-001 and mid pipe p/n 13755-003 repaired by Aerospace Welding Minneapolis on work orders 209435 and 209436. Reinstalled exhaust system using new gaskets p/n 652458. Replaced valve cover gaskets for nbr1/3/4/5 cylinders using new gaskets p/n 668893. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. —end-		-	+	+				
Removed, cleaned, tested and reinstalled all spark plugs. Replaced airfilter element with new element p/n BA-24. Compression check 1-70/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n AA48109 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Removed exhaust system. Collector p/n 13535-001 and mid pipe p/n 13755-003 repaired by Aerospace Welding Minneapolis on work orders 209435 and 209436. Reinstalled exhaust system using new gaskets p/n 652458. Replaced valve cover gaskets for nbr1/3/4/5 cylinders using new gaskets p/n 668893. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has	Removed, cleaned, tested and reinstalled all spark plugs. Replaced airfilter element with new element p/n BA-24. Compression check 1-70/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n AA48109 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Removed exhaust system. Collector p/n 13535-001 and mid pipe p/n 13755-003 repaired by Aerospace Welding Minneapolis on work orders 209435 and 209436. Reinstalled exhaust system using new gaskets p/n 652458. Replaced valve cover gaskets for nbr1/3/4/5 cylinders using new gaskets p/n 668893. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. —end-		N880CE)	S/N 6	86366	05/20/2022		
p/n BA-24. Compression check 1-70/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n AA48109 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Removed exhaust system. Collector p/n 13535-001 and mid pipe p/n 13755-003 repaired by Aerospace Welding Minneapolis on work orders 209435 and 209436. Reinstalled exhaust system using new gaskets p/n 652458. Replaced valve cover gaskets for nbr1/3/4/5 cylinders using new gaskets p/n 668893. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has	p/n BA-24. Compression check 1-70/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for the day was 46. Performed boroscope inspection of all 6 cylinders, no defects noted. Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n AA48109 and serviced engine with Aeroshell 15w-50w oil. Added 1 pint of CamGuard. Removed exhaust system. Collector p/n 13535-001 and mid pipe p/n 13755-003 repaired by Aerospace Welding Minneapolis on work orders 209435 and 209436. Reinstalled exhaust system using new gaskets p/n 652458. Replaced valve cover gaskets for nbr1/3/4/5 cylinders using new gaskets p/n 668893. Ran engine and performed leak check no leaks noted. Installed engine cowling. All AD's current as of this date. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. —end-	0	Hobbs:	2053.5		total	2053.5	0.0	
thin Adres			p/n BA- the day oil, rem engine 13535- 209435 gaskets	-24. Com y was 46. noved an with Aer -001 and 5 and 209 s for nbr	pression Performed d inspect roshell 15 mid pipe 9436. Reid 1/3/4/5 c	check 1-7 ed borosc ed oil filte w-50w oil p/n 1375 nstalled ex ylinders u	o/80, 2-64/80, 3-68/80, 4-70/80, 5-68/80, 6-70/80. Min pressure for ope inspection of all 6 cylinders, no defects noted. Drained engine or no defects noted. Installed new oil filter p/n AA48109 and serviced land. Added 1 pint of CamGuard. Removed exhaust system. Collector p/n 5-003 repaired by Aerospace Welding Minneapolis on work orders exhaust system using new gaskets p/n 652458. Replaced valve cover sing new gaskets p/n 668893. Ran engine and performed leak check owling. All AD's current as of this date. I certify that this engine has an Annual inspection and found to be Airworthy. —end-		

Date	Total	Time	1	Since verhaul	Engine Service and Mainten	ance Record
	Hrs.	Min.	Hrs.	Min.	Installations, Inspections, Airworthiness Directive Modifications and Service Bulletins	s, Special Inspections,
Brought Forward		-				Al .5
N880CD	S,	/N 6863	66 D	ecembe	11, 2016	
1 11 4015			-4-1.1012	. 7		**************************************
——— Hobbs:1913	3.7	τ	otal:1913		-	
					and reinstalled all spark plugs with new	
					for Overhaul. Bothn mags O/H by Quality	
					38 S/N H039806DR. Right mag on W/O 021189 /H and timed to Engine. Replaced the ignition	
					4-25. Removed and reinstalled the nbrs 1,3,2,4	
	1.00				ace the magnetos and ignition harness.	
					p/n BA-24. Compression check 1-74/80, 2-	
					Ain pressure for the day was 44. Drained engine _ ts noted. Installed new oil filter p/n CH48109-1	
					oil. Ran engine and performed leak check no	
100/MINE 100 2008 St 105	_				s current as of this date. I certify that this	
engine has	been ins	spected	in accord	ance wit	h an Annual inspection and found to be	
Airworthy.	–end-				H. Shan	
				٥	Stewart Pruitt 2644624 A&P/IA	
Nesoco		0/21.00				
N880CD		S/N 68	6366	January	26, 2018	
——— Hobbs:19	50.2		total:19	50.2		
Removed	. cleane	d insner	rted gan	and tost	ed and reinstalled all spark plugs with new	
gaskets. F	Replaced	all four	engine c	ounts wit	th new Lord Mounts p/n J-9613-54 batch nbr	
00119091	.89. кер	aired cra	acks int e	hleft fror	it bafflings. Replaced airfilter element with now	
element t	7/1 BA-2	4. Comp	ression c	heck 1-7	6/80, 2-74/80, 3-76/80, 4-74/80, 5-76/80, 6	
no defects	in pressi s noted	ure for t	he day w	as 46. Di	rained engine oil, removed and inspected oil filter	
15w-50w	oil. Adde	ed 1 pint	of Came	iliter p/n Guard Ra	CH48109-1 and serviced engine with Aeroshell an engine and performed leak check no leaks	
noted. Ins	talled er	ngine co	wling. Al	I AD's cu	rrent as of this date I certify that this ongine has	
been inspe	ected in	accorda	nce with	an Annu	al inspection and found to be Airworthy -end-	
				,	The June Stewart Pruitt 2644624 A&P/IA	
	 	 			Stewart Fullt 2044024 AQP/IA	
			9			
			3			
Į.	1	1	1	l		

Date	Total	Time	Time		Engine Service and Maintenance	e Record
	Hrs.	Min.	Last Ov Hrs.	/emaui Min.	Installations, Inspections, Airworthiness Directives, Spe	
Brought Forward	1113.	IVIIII.	1110.	141111.	Modifications and Service Bulletins	
brought rotward						
N880CD		/N 300	(O ctober 5	Hugast 30, WH	
—— Hobbs: / Ø						
Removed er 14554-001.					nbr4 cylinder EGT probes with new probes Cirrus p/n	
					Stewart Pruitt 2644624 A&P	However, a second
	1	1	,			
N8800	CD	S/N	686366	Nov	rember 13, 2014	
Hobbs	s:1819.8		tota	1:1819.8		
gasker Comp the da inspec engine p/n 14 indica date.	ts. Check ression and was 4 cted oil for the with A 4880-00 ation ops I certify	ked mag check 1- 2, c/w b filter no eroshell 1. Ran e s normal that this	rneto timi 70/80, 2- oroscope defects n 15w-50v ngine and	ing. Repla 72/80, 3 inspecti oted. Ins v oil. Rep d perforn he run. In nas been	tested and reinstalled all spark plugs with new acced airfilter element with new element p/n BA-2470/80, 4-56/80, 5-70/80, 6-70/80. Min pressure for ion of nb4 cylinder. Drained engine oil, removed and stalled new oil filter p/n CH48109-1 and serviced placed nbr6 cylinder CHT probe with new probe Cirrus and leak check no leaks noted. Nbr 6 cylinder CHT istalled engine cowling. All AD's current as of this inspected in accordance with an Annual inspection Stewart Pruitt 2644624 A&P/IA	
N88	BOCD	S,	/N 68636	6 N	ovember 20, 2015	
Hob	bs:1866	5.7	to	tal:1866.	.7	
gasl	kets. Che	ecked m	agneto ti	ming. Re	d, tested and reinstalled all spark plugs with new placed airfilter element with new element p/n BA-24. 3-72/80, 4-70/80, 5-56/80, 6-68/80. Min pressure for	
the	day was	44, c/w	borosco	pe insped	ction of nb5 cylinder. Drained engine oil, removed and installed new oil filter p/n CH48109-1 and serviced	
eng	ine with	Aerosh	ell 15w-50	0w oil. R	eplaced nbr 1 ALT with new Alternator and drive Hub	
					46843 S/N 009HA054. Ran engine and performed leak e cowling. All AD's current as of this date. I certify that	
					ordance with an Annual inspection and found to be	
Airv	vorthy	end-			Steen fun	
					Stewart Pruitt 2644624 A&P/IA	
	-	-	+		2.8	
	+	+	 	 		

Date	8	Total	Time	Time S		Engine Service and Man-	
		Hrs.	Min.	Hrs.	Min.	Installations, Inspections, Airworthiness Directives, Special Inspections and Service Bulletins	
Brought Forwar	ď	L	→				
	N8	80CD	ç	5/N 68636	6	August 18, 2011	
3	Ho	bbs: 16	22.5	Т	otal:162	2.5	
	p/ te in 70 pr er	n AA481 sted and stalled e 0/80, 6-7 ump O/F	.09 and I reinsta Hement 10/80 m I by Airc I leak ch s been i	serviced of the serviced of th	engine warkplugs Compare for the ssories of the second contractions are second contractions.	ith Aeroshell 15w-50w. Removed, cleaned, inspected, ith Aeroshell 15w-50w. Removed, cleaned, inspected, ith Checked magneto timing. Replaced airfilter element, ression check 1-72/80, 2-70/80, 3-64/80, 4-66/80, 5-e day was 40. Removed fuel pump due to leaking. Fuel f OKC on W/O 47464. Installed fuel pump, ran engine and led. All AD's current as of this date. I certify that this clance with an Annual inspection and found to be	
						Alun Dan 7644624	
						Stewart Pruitt 2644624 A&P/I.A.	
- 1							
		N880CD	İ	S/N 686	5366	September 7, 2012	
		Hobbs:1	701.2		total:17	701.2	
		magnet Cleaned separat no defe check n this eng Airwort	o timing I and res or, clear octs note o leaks i gine has chy. —end	g. Compre seated con ned and re d. Installe noted. Ins been insp d-	ssion che nnectors eassembled new o talled en ected in	pped, tested and reinstalled all spark plugs. Checked eck 1-74/80, 2-68/80, 3-72/80, 4-72/80, 5-70/80, 6-70/80. for the nbr2 CHT probe. Disassembled the Airwolf air/oil led the air/oil separator. Removed and inspected oil filter il filter p/n CH48109-1. Ran engine and performed leak agine cowling. All AD's current as of this date. I certify that accordance with an Annual inspection and found to be ###################################	
		N880 -	CD	S/N	686366	October 5,2013	
		Remo gaske 70/80 air/oi Instal engin	ets. Checonomics.	aned, insp ked magn 30 Disass tor. Drain oil filter p erformed certify tha	pected, g eto timil sembled ed engin o/n CH48 leak chea at this en	capped, tested and reinstalled all spark plugs with new ng. Compression check 1-70/80, 2-70/80, 3-70/80, 4-60/80, 5-the Airwolf air/oil separator, cleaned and reassembled the e oil, removed and inspected oil filter no defects noted. 109-1 and serviced engine with Aeroshell 15w-50w oil Ranck no leaks noted. Installed engine cowling. All AD's current as ngine has been inspected in accordance with an Annual worthy. —end-	

	TOtal	Time		e Since Overhaul	Engine Service and Maintenance Record
	Hrs.	Min.	Hrs.	Min.	Installations, Inspections, Airworthiness Directives, Special Inspections, Modifications and Service Bulletins
ard		→			Wisdingarous and Service Bulletins
L	1470	00	1470	2	Orain Engine oil Removed Truspet 1
					oil filter No Defects noted, Installed
					New oil Filter PIN AA 48109, Serviced
_					
					Engine with Acrosholl 150-150. Ran Engine and performed hoak che us hooks what
					Installed Coaling - end - Standbout 3694624 1
					30 7 96 29 M
Durand and engi	ing compi nbr5 cylin 5 cylinden ne and pe	rk plug ression nder anders. Com	s p/n UR check fo d had rep apression	HB32E. In pund nbr1 paired by check 1-	cected oil filter no defects noted. Installed new oil filter p/n croshell 15w-50w. Removed all spark plugs and installed 12 Replaced air filter element, installed new BA24 element. and nbr5 cylinder exhaust valves leaking. Removed nbr1 Graham Aircraft engines on w/o 10 130. Reinstalled nbr1 -70/80, 2-72/80, 3-70/80, 4-72/80, 5-70/80, 6-68/80. Ran aks noted. All AD's current as of this date. I certify that dance with an Annual inspection and found to be
					Alex Gree 2644674 I.A.
					Stewart Pruitt 2644624 I.A.
					Stewart Pruitt 2644624 I.A.
880CD)		01/24	/2011	Stewart Pruitt 2644624 I.A.
			01/24	/2011	Stewart Pruitt 2644624 I.A.
emove estalled o defer eroshe	1580.4 ed engine d new Sai cts noted ell 15w-50	f-Air qu . Install)w oil. F	g. Remov ick drain ed new d	/ed oil dra p/n S625 oil filter p, ne and pe	ain plug and drained engine oil. 50. Removed and inspected oil filter /n AA48109 and serviced engine with rformed leak check, no leaks noted. o AVL for oil analysis. —end-
nstalled o defed eroshe	1580.4 ed engine d new Sai cts noted ell 15w-50	f-Air qu . Install)w oil. F	g. Remov ick drain ed new d	/ed oil dra p/n S625 oil filter p, ne and pe	ain plug and drained engine oil. 50. Removed and inspected oil filter /n AA48109 and serviced engine with rformed leak check, no leaks noted. to AVL for oil analysis. —end-
emove estalled o defed eroshe	1580.4 ed engine d new Sai cts noted ell 15w-50	f-Air qu . Install)w oil. F	g. Remov ick drain ed new d	/ed oil dra p/n S625 oil filter p, ne and pe	ain plug and drained engine oil. 50. Removed and inspected oil filter /n AA48109 and serviced engine with rformed leak check, no leaks noted. o AVL for oil analysis. —end-
obbs:1 emove stalled o defer eroshe	1580.4 ed engine d new Sai cts noted ell 15w-50	f-Air qu . Install)w oil. F	g. Remov ick drain ed new d	/ed oil dra p/n S625 oil filter p, ne and pe	ain plug and drained engine oil. 50. Removed and inspected oil filter /n AA48109 and serviced engine with rformed leak check, no leaks noted. to AVL for oil analysis. —end-
obbs:1 emove stalled o defect eroshe	1580.4 ed engine d new Sai cts noted ell 15w-50	f-Air qu . Install)w oil. F	g. Remov ick drain ed new d	/ed oil dra p/n S625 oil filter p, ne and pe	ain plug and drained engine oil. 50. Removed and inspected oil filter /n AA48109 and serviced engine with rformed leak check, no leaks noted. to AVL for oil analysis. —end-
obbs:1 emove istalled o defed eroshe	1580.4 ed engine d new Sai cts noted ell 15w-50	f-Air qu . Install)w oil. F	g. Remov ick drain ed new d	/ed oil dra p/n S625 oil filter p, ne and pe	ain plug and drained engine oil. 50. Removed and inspected oil filter /n AA48109 and serviced engine with rformed leak check, no leaks noted. to AVL for oil analysis. —end-
obbs:1 emove istalled o defed eroshe	1580.4 ed engine d new Sai cts noted ell 15w-50	f-Air qu . Install)w oil. F	g. Remov ick drain ed new d	/ed oil dra p/n S625 oil filter p, ne and pe	ain plug and drained engine oil. 50. Removed and inspected oil filter /n AA48109 and serviced engine with rformed leak check, no leaks noted. to AVL for oil analysis. —end-
obbs:1 emove stalled o defer eroshe	1580.4 ed engine d new Sai cts noted ell 15w-50	f-Air qu . Install)w oil. F	g. Remov ick drain ed new d	/ed oil dra p/n S625 oil filter p, ne and pe	ain plug and drained engine oil. 50. Removed and inspected oil filter /n AA48109 and serviced engine with rformed leak check, no leaks noted. to AVL for oil analysis. —end-
obbs:1 emove stalled o defer eroshe	1580.4 ed engine d new Sai cts noted ell 15w-50	f-Air qu . Install)w oil. F	g. Remov ick drain ed new d	/ed oil dra p/n S625 oil filter p, ne and pe	ain plug and drained engine oil. 50. Removed and inspected oil filter /n AA48109 and serviced engine with rformed leak check, no leaks noted. to AVL for oil analysis. —end-
obbs:1 emove istalled o defed eroshe	1580.4 ed engine d new Sai cts noted ell 15w-50	f-Air qu . Install)w oil. F	g. Remov ick drain ed new d	/ed oil dra p/n S625 oil filter p, ne and pe	ain plug and drained engine oil. 50. Removed and inspected oil filter /n AA48109 and serviced engine with rformed leak check, no leaks noted. to AVL for oil analysis. —end-
emove estalled o defed eroshe	1580.4 ed engine d new Sai cts noted ell 15w-50	f-Air qu . Install)w oil. F	g. Remov ick drain ed new d	/ed oil dra p/n S625 oil filter p, ne and pe	ain plug and drained engine oil. 50. Removed and inspected oil filter /n AA48109 and serviced engine with rformed leak check, no leaks noted. to AVL for oil analysis. —end-

	Date Total Tim			Since verhaul	Engine Service and Maintenance Record			
	Hrs.	Min.	Hrs.	Min.	Installations, Inspections, Airworthiness Directives, Special Inspections, Modifications and Service Bulletins			
Brought Forward		→						
— N880CD — Hobbs: 1			S/N 68	36366 1328.2	June 27, 2008			
tested an 74/80, 3- p/n BA-2 AD's cur	9-1 and dreinst 70/80, 24. Ran rrent as	talled a 4-76/8 engine of this	noved and ed engine of the sparkp of the spa	nd inspect e with A blugs. Ch /80, 6- 6 formed I certify th	ted oil filter no defects noted. Installed new oil filter p/n deroshell 15w-50w. Removed, cleaned, inspected, gapped, necked magneto timing. Compression check 1- 68/80, 2- 66/80. Replaced air filter element, installed new element leak check, no leaks noted. Installed engine cowling. All nat this engine has been inspected in accordance with an worthy. –end- Stewart Pruitt 2644624 I.A.			
	ushing l	P/N: 50		1 in left	July 8, 2008 flap hinge control tube. Installed Bracket P/N: 21579- be in left side engine baffling, and installed 1" scat **Scale of the Control of the C			
Drain	os: 1377 ned engi AA4801	ne oil, re 9. Servi	ced engir	and inspec	cted oil filter no defects noted. Installed new oil filter deroshell 15-50w oil . Ran engine and performed leak the cowling. –end-			
				i	Stewart Pruitt 2644624 A&P			
2/5/49			Task	1/21	Stewart Pruitt 2644624 A&P			
2/5/09	5.0			illed	Now hattery - Concord RG-L4151			
2/5/09	5,0		Insh		New hattery - Concord RG-L4151271607			
2/5/09 2/5/09	5,0				Now hattery - Concord RG-L4151			

Time Since **Total Time Engine Service and Maintenance Record** Date Last Overhaul Installations, Inspections, Airworthiness Directives, Special Inspections, Hrs. Min. Hrs. Min. Modifications and Service Bulletins **Brought Forward** January 4, 2007 N880CD Hobbs: 1157.0 Drained engine oil, removed and inspected oil filter, no defects noted. Installed new oil filter p/n AA48109 and serviced engine with Aeroshell 15w-50w. Removed, cleaned, inspected, gapped and tested all spark plugs. Reinstalled all spark plugs. Repaired wire for the NBR 6 cylinder CHT probe. Ran engine and performed leak check, no leaks noted. -end-Standefundes 2644624 Hel Stewart Pruitt 2644624 A&P June 05, 2007 N880CD Hobbs: 1202.3 Drained engine oil, removed and inspected oil filter no defects noted. Installed new AA48109 oil filter. Checked magneto timing. Removed, cleaned, inspected, gapped and tested all sparkplugs. Replaced air filter element, installed new BA24. Serviced the engine with Aeroshell 15w-50w. Compression check 1-72/80, 2-72/80, 3-72/80, 4-70/80, 5-70/80, 6-74/80. Ran engine and performed leak check no leaks noted. I certify that this engine has been inspected in accordance with an Annual inspection and found to be Airworthy. -end-Lune Sunto 26446 24 I.A Stewart Pruitt 2644624 IA November 16, 2007 N880CD Hobbs: 1260.2 Drained engine oil, removed and inspected oil filter no defects noted. Installed new oil filter p/n AA48108 and serviced engine with Aeroshell 15w-50. Replaced terminal for Nbr 6b cylinder CHT probe. Ran engine and preformed leak check and ops check of Nbr 6 cylinder CHT ind. Cht inds normal and leak check good. Installed engine cowling. - end-Atunto Sunte 2644674 Aas Stewart Pruitt 2644624 A&P

35

cl

Date	Total	Time	80 1921 20 10 1	Time Since Last Overhaul Installations, Inspections, Airworthiness Directives, Special Inst					
	Hrs.	Min.	Hrs.	Min.	Modifications and Service Bulletins	pooles more and			
Brought Forward		->							
Hobbs:206	54.3		total:20	64.3					
Removed,	cleaned	, tested a	ind reinsta	alled all sp	ark plugs. Replaced airfilter element with new element 0, 3-68/80, 4-70/80, 5-68/80, 6-68/80. Min pressure for				
4 1	AC Do	rformed	harascan	e inspectio	on of all 6 cylinders, no defects noted. Drained engine				
all warment	and and it	nenorted	nil filter r	o defects	noted. Installed new oil filter p/n AAA8.103 and services				
	th Aaras	hall 15w	50w oil A	dded 1 pi	nt of CamGuard. Removed Airwolf Air/oll Separator,				
disassemi	bled, dea	ened and	reassemb	ded. Repai	ired crack in the left side aft engine baffle. Reinstalled eak check no leaks noted. Installed engine cowling. All				
air/oil sep	parator.	Ran engi	ne and pe o. I certify	that this e	engine has been inspected in accordance with an Annual				
inspection	n and for	and to be	Airworth	y. –end-	L 26				
Пэрсско	ir aria ra			-	Stewart Pruitt 2644624 A&P/IA 6/11/2023				
	1			1					
		+				· .			
		+	_						
	-								
		-	-						
			_						
					_				
	_								
					1				
	-								
	_	_	-						
	-		+-						
		_	-						
	_	_							